



NMCB-1 & NMCB-2
support 1 to 6 NM
cables & low voltage
cables. NMCB-1 may
also be used with up to
4 AC or MC cables

NMCB-3
supports 1 to 5
AC or MC cables on
wood or metal studs
and concrete blocks

895-MC
galvanized steel
bracket for 1 to 4
AC or MC cables

733-PS
protector strips
for non-metallic
sheath cables

**NMLV-100
NMLV-200**
single gang &
double gang
low-voltage new
work device holders

Bridgeport quality for every job.

BRIDGEPORT

Supports and more

Here's a sampling of the newest from
Bridgeport's full line of supports,
brackets and device holders.



Bridgeport quality goes beyond fittings

Features

- NMCB-1 provides maximum flexibility for positioning a maximum of six 14/2 to 10/3 NM-B cables or four 14/2 to 12/2 AC/MC cables. Also suitable for low-voltage cabling. Includes screws for wood or metal studs.
- NMCB-2 accommodates a single 14/2 to 10/3 NM cable or two 14/2 NM cables in each of three slots. The low-profile, self-locking design prevents accidental cable removal. Packaged with nails for wood studs or furring strips.
- NMCB-3 holds up to five 14/2 to 10/3 AC or MC cables with a low profile design that features unique dimpled slots that prevent accidental cable removal. Includes nails for installation on wood stud or furring strip, and may also be screw mounted to steel stud or concrete block wall.
- 895-MC positions a maximum of four 14/2, 14/3, 14/4, 12/2 or 12/3 AC or MC cables with galvanized steel construction and a convenient slot for nailing or screwing into place.
- 733-PS provides physical protection for non-metallic sheath or low voltage cabling within walls. The three-foot length zinc electroplated protectors feature slots to secure cables.
- NMLV-100F and NMLV-200F attach to new-work wood or steel studs and furring strips to secure low-voltage devices.
- NMLV-100B and NMLV-200B attach to new-work studs to secure low-voltage devices and 1/2" or 3/4" EMT.

Catalog Number	UPC Number	Trade Size	Unit Quantity	Standard Package	Lbs./C Pcs.
NMCB-1	40447	---	25	100	3.5
NMCB-2	40757	---	25	100	3.5
NMCB-3	40767	---	25	100	3.5
895-MC	02895	---	50	500	6.1
733-PS	00733	---	---	20	98.5
NMLV-100F	42738	Single Gang	10	100	13.7
NMLV-100B	42739	Single Gang	10	100	19.6
NMLV-200F	44738	Double Gang	5	50	16.6
NMLV-200B	44739	Double Gang	5	50	22.6

