



# SEE

THE DIFFERENCE

# LIQUID TIGHT FITTINGS

## Liquid Tight Connectors



Nonmetallic straight and 90° connectors for use with nonmetallic "Type B" liquid tight conduit. PVC with zinc die cast locknut.

File No. E9391

### Straight Nonmetallic

Cat. No.	Trade Size
429-NMLT	3/8"
430-NMLT	1/2"
431-NMLT	3/4"
432-NMLT	1"
433-NMLT	1 1/4"
434-NMLT	1 1/2"
435-NMLT	2"

### 90° Nonmetallic

Cat. No.	Trade Size
469-NMLT	3/8"
470-NMLT	1/2"
471-NMLT	3/4"
472-NMLT	1"
473-NMLT	1 1/4"
474-NMLT	1 1/2"
475-NMLT	2"

## Screw-On Liquid Tight Connectors, Straight & 90°



Nonmetallic straight and 90° connectors for use with nonmetallic "Type B" liquid tight conduit. Connectors simply screw onto conduit. No tools required! Sunlight resistant.

File No. E9391

### Straight Nonmetallic

Cat. No.	Trade Size
430-NMLTS	1/2"
431-NMLTS	3/4"

### 90° Nonmetallic

Cat. No.	Trade Size
470-NMLTS	1/2"
471-NMLTS	3/4"

## Liquid Tight Connectors, 90°



For use with metallic and nonmetallic "Type B" liquid tight conduit.

File No. E9391, File No. LR39354

### Zinc Die Cast

Cat. No.	Trade Size
469-LT2	3/8"
470-LT2	1/2"
471-LT2	3/4"
472-LT2	1"
473-LT2	1 1/4"

### Zinc Die Cast/Insulated Throat-105°C

Cat. No.	Trade Size
469-LTI2	3/8"
470-LTI2	1/2"
471-LTI2	3/4"
472-LTI2	1"
473-LTI2	1 1/4"

### Cast Zinc

Cat. No.	Trade Size
474-LT2	1 1/2"
475-LT2	2"
476-LT2	2 1/2"
477-LT2	3"
478-LT2	3 1/2"
479-LT2	4"

### Cast Zinc/Insulated Throat-105°C

Cat. No.	Trade Size
474-LTI2	1 1/2"
475-LTI2	2"
476-LTI2	2 1/2"
477-LTI2	3"
478-LTI2	3 1/2"
479-LTI2	4"

## Liquid Tight Connectors, Straight



For use with metallic liquid tight conduit.

File No. E9391

\*Note: UL Listing not applicable to 5" & 6" Malleable Iron.

### Steel

Cat. No.	Trade Size
429-SLT	3/8"
430-SLT	1/2"
431-SLT	3/4"
432-SLT	1"

### Steel/Insulated Throat-105°C

Cat. No.	Trade Size
429-SLTI	3/8"
430-SLTI	1/2"
431-SLTI	3/4"
432-SLTI	1"

### Malleable Iron

Cat. No.	Trade Size
429-MLT	3/8"
430-MLT	1/2"
431-MLT	3/4"
432-MLT	1"
433-SLT	1 1/4"
434-SLT	1 1/2"
435-SLT	2"
436-SLT	2 1/2"
437-SLT	3"
438-SLT	3 1/2"
439-SLT	4"
440-SLT	5"
441-SLT	6"

### Malleable Iron/Insulated Throat-105°C

Cat. No.	Trade Size
429-MLTI	3/8"
430-MLTI	1/2"
431-MLTI	3/4"
432-MLTI	1"
433-SLTI	1 1/4"
434-SLTI	1 1/2"
435-SLTI	2"
436-SLTI	2 1/2"
437-SLTI	3"
438-SLTI	3 1/2"
439-SLTI	4"
440-SLTI	5"
441-SLTI	6"

## Liquid Tight Connectors, Straight



For use with metallic and nonmetallic "Type B" liquid tight conduit.

File No. E9391, File No. LR39354

### Zinc Die Cast

Cat. No.	Trade Size
429-LT2	3/8"
430-LT2	1/2"
431-LT2	3/4"
432-LT2	1"
433-LT2	1 1/4"
434-LT2	1 1/2"
435-LT2	2"
436-LT2	2 1/2"
437-LT2	3"
438-LT2	3 1/2"
439-LT2	4"

### Zinc Die Cast/Insulated Throat-105°C

Cat. No.	Trade Size
429-LTI2	3/8"
430-LTI2	1/2"
431-LTI2	3/4"
432-LTI2	1"
433-LTI2	1 1/4"
434-LTI2	1 1/2"
435-LTI2	2"
436-LTI2	2 1/2"
437-LTI2	3"
438-LTI2	3 1/2"
439-LTI2	4"

# LIQUID TIGHT FITTINGS

## Liquid Tight Connectors, 45°



Malleable iron: For use with metallic liquid tight conduit.  
Cast zinc: For use with both metallic and nonmetallic "Type B" liquid tight conduit.

UL File No. E9391, SP File No. LR39354

### Malleable Iron

Cat. No.	Trade Size
449-SLT	3/8"
450-SLT	1/2"
451-SLT	3/4"
452-SLT	1"
453-SLT	1 1/4"
455-SLT	1 1/2"
455-SLT	2"
456-SLT	2 1/2"
457-SLT	3"
458-SLT	3 1/2"
459-SLT	4"

### Malleable Iron/Insulated Throat-105°C

Cat. No.	Trade Size
449-SLTI	3/8"
450-SLTI	1/2"
451-SLTI	3/4"
452-SLTI	1"
453-SLTI	1 1/4"
455-SLTI	1 1/2"
455-SLTI	2"
456-SLTI	2 1/2"
457-SLTI	3"
458-SLTI	3 1/2"
459-SLTI	4"

## Liquid Tight Connectors, 90°



For use with metallic liquid tight conduit.

UL File No. E9391, SP File No. LR39354: Steel

### Steel

Cat. No.	Trade Size
469-SLT	3/8"
470-SLT	1/2"
471-SLT	3/4"
472-SLT	1"
473-SLT	1 1/4"
474-SLT	1 1/2"
475-SLT	2"

### Steel/Insulated Throat-105°C

Cat. No.	Trade Size
469-SLTI	3/8"
470-SLTI	1/2"
471-SLTI	3/4"
472-SLTI	1"
473-SLTI	1 1/4"
474-SLTI	1 1/2"
475-SLTI	2"

### Malleable Iron

Cat. No.	Trade Size
476-SLT	2 1/2"
477-SLT	3"
478-SLT	3 1/2"
479-SLT	4"

### Malleable Iron/Insulated Throat-105°C

Cat. No.	Trade Size
476-SLTI	2 1/2"
477-SLTI	3"
478-SLTI	3 1/2"
479-SLTI	4"

## Combination Couplings



Coupling used to join either metallic or nonmetallic "Type B" liquid tight to EMT. Concrete-tight. UL Listed "Raintight".

UL File No. E9391

SP File No. LR39354

### Zinc Die Cast

Cat. No.	LT Trade Size	Rigid Trade Size
4360-DC	1/2"	1/2"
4361-DC	3/4"	3/4"

## Raintight Combination Couplings



Used to join rigid or IMC to metallic liquid tight conduit. Concrete-tight.

UL File No. E9391

### Steel

Cat. No.	LT Trade Size	Rigid Trade Size
4369-LT	3/8"	1/2"
4370-LT	1/2"	1/2"
4371-LT	3/4"	3/4"
4372-LT	1"	1"
4373-LT	1 1/4"	1 1/4"
4374-LT	1 1/2"	1 1/2"
4375-LT	2"	2"

## Liquid Tight Sealing Rings



Provides liquid tight sealing with connector to box or enclosure.

UL File No. E11259

### Polyethylene/Steel Retainer

Cat. No.	Trade Size
SR-050	1/2"
SR-075	3/4"
SR-100	1"
SR-125	1 1/4"
SR-150	1 1/2"

### Polyethylene/Steel Retainer

Cat. No.	Trade Size
SR-200	2"
SR-250	2 1/2"
SR-300	3"
SR-350	3 1/2"
SR-400	4"

## Push-On, Swivel Type Multi-Angle Connectors 0-90°



Push-on, multi-angle connectors for nonmetallic "Type B" liquid tight conduit. Simply push the connector into the conduit and tighten the domed sealing nut. Molded of Type 6 nylon. Resists salt water, weak acids, gasoline, alcohol, oil, grease, and many common solvents.

UL File No. E9391

### Nonmetallic

Cat. No.	Trade Size
480-NMLTS	1/2"
481-NMLTS	3/4"



Printed in the U.S.A.



BP-069 5000 0615