

## Armored and Metal Clad Cable

### Whipper-Snap® Single Screw Strap Type Connector for MCI-A Cable



Used to connect 14/2 (.38" Ø min) to 10/4 (.61" Ø max) to box or enclosure.

File No. E20534

#### Zinc Die Cast

Catalog Number	Trade Size	K.O. Size	MCI-A Cable Range		Unit Qty.	Std. Pkg. Qty.
			Min.	Max.		
BL16MCIA	3/8"	1/2"	.38"	.61"	50	500



### Multi-Purpose Connector Two Screw, Strap Type



Used to connect 14/2 to 12/2 nonmetallic sheath cable (NM-B), steel/aluminum 14/2 to 12/2 armored cable (AC), or metal clad (MC) cable, or steel/aluminum 3/8" flexible metal conduit to 1/4" knockout. Will fit 1/4" knockouts with flats, such as used in lighting applications.

Recognized UL File No. E9391

#### Zinc Die Cast

Catalog Number	Trade Size	K.O. Size	Unit Qty.	Std. Pkg. Qty.
563-DC2	1/4"	1/4"	50	500

### Combination Couplings



Coupling used to join duplex 14/2 to 10/3 armored or metal clad cable to 3/4" EMT. Set screw type transitional fitting ideal for commercial and institutional facilities. A labor savings, compared to the traditional junction box installation. Simply remove the armor and expose the length of conductors to reach the device box or enclosure. 14/2 to 10/3 AC/MC cable. Patent Pending.

#### Zinc Die Cast

Catalog Number	Trade Size	K.O. Size	Unit Qty.	Std. Pkg. Qty.
4157-DC	1/2"	3/4"	25	100