

## Zinc Plated Steel

Catalog Number	Trade Size	Unit Qty.	Std. Pkg. Qty.
EC-075	3/4"	15	60
EC-100	1"	10	40
EC-125	1-1/4"	8	40
EC-150	1-1/2"	6	30
EC-200	2"	---	4
EC-250	2-1/2"	---	1
EC-300	3"	---	1
EC-350	3-1/2"	---	1
EC-400	4"	---	1

**2-1/2" thru 4" suitable for use with EMT or rigid conduit.**

## Steel Expansion Couplings for EMT



Low cost and easy to use. Assembles like a regular EMT set screw coupling. Use to compensate plus or minus 2" lateral movement of conduit in dry locations. Available for use with trade size 3/4" thru 4" steel EMT. To install simply slide coupling end stop onto fixed end of EMT and tighten set screw. Place movable EMT completely into coupling and mark engagement, remove EMT and mark half the distance of engagement, reinstall EMT to half distance. May be used with **optional Bonding Jumper Assembly cat. nos. BJ-100, BJ-200 and BJ-400.**

US Patent 6,715,803,B1

 File No. E24001

## Intumescent

Catalog Number	Cartridge Size	Unit Qty.	Std. Pkg. Qty.
FS-1000	10.5 fluid ounces	1	12

## Firestop



Commercial grade quality intumescent. A water-based, non-corrosive, non-toxic, odorless compound that withstands 3000°F for 8 hours. Adheres to most construction materials including ceramics, composites, masonry, metal, plastic and wood. Can be safely removed with soap and water prior to curing. Paintable and sandable.

Classified by Underwriters Laboratories as a non-combustible product in compliance with zero flame and zero smoke index. ASTM-E136 non combustible. ASTM-E119 compliant. ASTM-E84 zero flame/zero smoke. ASTM-E814 compatible.

 File No. R25422